



MARK	DATE	DESCRIPTION	DESIGN

1. PART NO. LEGEND:
 8.26A0.***200
 ① ② ③ ④ ⑤
- ①.SERIES NAME:8.26A0-0.3MM FFC/FPC DUAL CONTACT SIDE CONNECTOR (H=1.1mm)
 ②.CONTACT PIN NUMBER:***=CONTACT PIN NUMBER
 ③.CONTACT AREA PLATING SPEC: GOLD PLATING: 2=1~3u";3=5u";4=10u";5=15u"
 SOLDER AREA PLATING SPEC: GOLD PLATING: 2=1~3u";3=5u";4=10u";5=15u"
 ④.UNSPECIFIED:0=NONSENSE
 ⑤.UNSPECIFIED:0=NONSENSE
2. PERFORMANCE:
 2.1: CURRENT RATING: 0.2A/PIN.
 2.2: VOLTAGE RATING: 30V (AC/DC).
 2.3: CONTACT RESISTANCE: INITIAL VALUE 100mOHM Max,
 2.4: INSULATION RESISTANCE: 50MOHM Min.
 2.5: DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR 1MINUTE;
 2.6: DURABILITY: 20 TIMES Min.
 2.7:OPERATING TEMPERATURE:-40C~+85C
 OPERATING HUMIDITY RANGE: 20% TO 85%

Pin Number	Part Number	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F
13	8.26A0.013200	5.40	4.23	3.60	3.00	4.90	4.20
15	8.26A0.015200	6.00	4.83	4.20	3.60	5.50	4.80
17	8.26A0.017200	6.60	5.43	4.80	4.20	6.10	5.40
19	8.26A0.019200	7.20	6.03	5.40	4.80	6.70	6.00
21	8.26A0.021200	7.80	6.63	6.00	5.40	7.30	6.60
23	8.26A0.023200	8.40	7.23	6.60	6.00	7.90	7.20
25	8.26A0.025200	9.00	7.83	7.20	6.60	8.50	7.80
27	8.26A0.027200	9.60	8.43	7.80	7.20	9.10	8.40
29	8.26A0.029200	10.20	9.03	8.40	7.80	9.70	9.00
31	8.26A0.031200	10.80	9.63	9.00	8.40	10.30	9.60
33	8.26A0.033200	11.40	10.23	9.60	9.00	10.90	10.20
35	8.26A0.035200	12.00	10.83	10.20	9.60	11.50	10.80
37	8.26A0.037200	12.60	11.43	10.80	10.20	12.10	11.40
39	8.26A0.039200	13.20	12.03	11.40	10.80	12.70	12.00
41	8.26A0.041200	13.80	12.63	12.00	11.40	13.30	12.60
45	8.26A0.045200	15.00	13.83	13.20	12.60	14.50	13.80
51	8.26A0.051200	16.80	15.63	15.00	14.40	16.30	15.60
57	8.26A0.057200	18.60	17.43	16.80	16.20	18.10	17.40
61	8.26A0.061200	19.80	18.63	18.00	17.40	19.30	18.60
71	8.26A0.071200	22.80	21.63	21.00	20.40	22.30	21.60

5	STATOR	PHOSPHOR BRONZE			2
4	TERMINAL II	PHOSPHOR BRONZE			POSITIONS
3	TERMINAL I	PHOSPHOR BRONZE			POSITIONS
2	COVER	THERMOPLASTIC UL94V-0	BLACK		1
1	HOUSING	THERMOPLASTIC UL94V-0	NATURAL		1
NO.	COMPONENTS	MATERIALS	FINISH/COLOR	SPECIFICATION	QUANTITY

DIANWEI 东莞市钿威电子科技有限公司
 DONGGUAN DIANWEI ELECTRONIC TECHNOLOGY CO., LTD
 Tel: +86-769-8788 8322 Fax: +86-769-8788 8321 E-mail: dianwei@188.com Http://www.dianwei.cn

UNLESS OTHERWISE SPECIFIED TOLERANCE

ANG	TOL	DIM	TOL
.X	±3.0°	.X	±0.20
.XX	±2.0°	.XX	±0.10
.XXX	±1.0°	.XXX	±0.05

APPROVED	VERIFIED	DESIGN	DRAWING NO	PART NAME:
			8.26A0-C	0.3MM FFC/FPC SWING COVER CONNECTOR(H=1.1mm)
				PART NO. 8.26A0.***200
				DATE 2021.09.13
				UNITS mm
				SCALE 1:1
				PAGE 1/1
				REV X1

NOTE: ALL RIGHTS RESERVED, BANNED COPY!